

INDUSTRIAL COMPONENT DATA

C22-DH-G-X1-K10 132443 EATON ELECTRIC

C22-DH-G-X1-K10

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DH-G-X1-K10



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DH-G-X1-K10
Catalog number	132443
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-028D1CE73C
Generated	2026-08-06

Product Overview

C22-DH-G-X1-K10

Pushbutton, Extended, momentary, 1 N/O, Screw connection, green, inscribed, Bezel: titanium

Pushbutton, RMQ Compact, Complete unit, Design: Extended, momentary, Connection type: Screw connection, button plate: green, Button plate inscribed, Name: I, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, Extended, momentary, 1 N/O, Screw connection, green, inscribed, Bezel: titaniumPushbutton, RMQ Compact, Complete unit, Design: Extended, momentary, Connection type: Screw connection, button plate: green, Button plate inscribed, Name: I, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660Delivery program

Product rangeRMQ CompactBasic functionPushbutton actuatorsSingle unit/Complete unitComplete unitDesignExtendedmomentaryConnection typeScrew connectionButton platebutton plategreenButton plateinscribedNameIDegree of ProtectionIP66, IP67, IP69Front ringBezel: titaniumConnection to

SmartWire-DTnoContactsN/O = Normally open1 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data

GeneralStandardsIEC/EN 60947-5-1

VDE 0660Lifespan, mechanical [Operations]> 5 x 106Operating frequency [Operations/h]? 3600Actuating force? 5

nClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69Ambient temperatureOpen-25 - +70 °CAmbient temperatureStorage- -30 - + 80 °CMounting positionAs requiredTerminal capacitiesSolid2 x 0.5 - 1.5_x mm2Terminal capacitiesFlexible with ferrule2 x 0.5 - 1.5_x mm2Tightening torque for terminal screw0.8 NmContactsRated impulse withstand voltage [Uimp]4000 V ACRated insulation voltage [Ui]250 VRated conditional short-circuit current [Iq]1 kAOv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DH-G-X1-K10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.