

INDUSTRIAL COMPONENT DATA

C22-DL-B-K10-24-P32 185577 EATON ELECTRIC Illuminated pushbutton actuator, classic, flat, tasted, 1 N/O, blu..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DL-B-K10-24-P32



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DL-B-K10-24-P32
Catalog number	185577
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-C52A981AA7
Generated	2026-08-05

Product Overview

Illuminated pushbutton actuator, classic, flat, tasted, 1 N/O, blue, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 1 m
Push-button light flush compact; 22 mm; Return; Blue; 24 V AC/DC; 1 NO; cable 1 m and connector M8
Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Cable (black) with M8 plug, 4 pole, 1 m, LED Blue, Blue, Blank, 24 V AC/DC, Bezel: titanium
Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Color LED: Blue, button plate: Blue, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Cable (black) with M8 plug, 4 pole, 1 m, LED Blue, Blue, Blank, 24 V AC/DC, Bezel: titanium
Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Colour LED: Blue, button plate: Blue, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660
Delivery program

Product rangeRMQ compact solutionBasic functionIlluminated pushbutton actuatorsSingle unit/Complete unitComplete unit
DesignFlatmomentaryConnection typeCable (black) with M8 plug, 4 poleCable Length1 mColourLEDLEDBlueButton

platebutton plateBlueButton plateBlankRated operational voltage LED24 V AC/DCNameNoneDegree of ProtectionIP66,
IP67, IP69 (front)
IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open1 N/OContact
sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data
GeneralStandardsIEC/EN 60947-5-1
VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]?
3600Actuating force? 5 nPlug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Degre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DL-B-K10-24-P32 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.