

INDUSTRIAL COMPONENT DATA

C22-DL-G-K10-24-P62 185586 Y7-185586 EATON ELECTRIC Illuminated pushbutton actuator, classic, flat, tasted, ..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DL-G-K10-24-P62



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DL-G-K10-24-P62
Catalog number	Y7-185586
Category	Push button, complete
Minimum order	1 unit
Document ID	EO-2FA66C0E2D
Generated	2026-08-06

Product Overview

Illuminated pushbutton actuator, classic, flat, tasted, 1 N/O, green, 24 V AC/DC, cable (black) with non-terminated end, 4 pole, 1 m

C22-DL-G-K10-24-P62

Eaton Moeller® series C22 Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Cable (black) with non-terminated end, 4 pole, 1 m, LED green, green, Blank, 24 V AC/DC, Bezel: titanium

Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 1 m, Color LED: green, button plate: green, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Number of command positions (EF001372)	1
Type of button (EF001546)	Flat
Colour button (EF000190)	Green
Transparent (EF006243)	No
Construction type lens (EF006253)	Round
Hole diameter (EF000079)	22.5 mm
Width opening (EF004565)	0 mm
Height opening (EF004778)	0 mm
Suitable for lighting (EF001142)	Yes

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Switching function latching (EF007447)	No
Spring-return (EF001407)	Yes
Supply voltage lamp (EF006522)	24 V
Number of contacts as normally open contact (EF008256)	1
Number of contacts as normally closed contact (EF008255)	0
Number of contacts as change-over contact (EF008257)	0
Type of electric connection (EF003961)	Cable
With front ring (EF006014)	Yes
Material front ring (EF005972)	Plastic
Colour front ring (EF002429)	Titanium
Degree of protection (IP) (EF005474)	IP67/IP69K
Degree of protection (NEMA) (EF011959)	12

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Illuminated pushbutton actuator Catalog Number 185586 Model Code C22-DL-G-K10-24-P62 EAN 4015081810802 Product Length/Depth 1060 mm Product Height 30 mm Product Width 30 mm Product Weight 0.051 kg Certifications CE

CSA

VDE 0660

UL

IEC/EN 60947-5-1

CSA Class No.: 321103

CSA File No.: 165628

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL File No.: E29184 Features & Functions

Bezel color Titanium Bezel material Plastic Design Flat

Classical Electric connection type Cable Fitted with: Front ring Inscription Blank Light color Green General

Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection NEMA 12

IP67/IP69K Mounting position As required Opening diameter 22.5 mm Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC

Shock resistance 30 g, Mechanical, Shock duration 11 ms Suitable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DL-G-K10-24-P62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.