

INDUSTRIAL COMPONENT DATA

C22-DL-R-K01-24 136626 EATON ELECTRIC C22-DL-R-K01-24

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DL-R-K01-24



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DL-R-K01-24
Catalog number	136626
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-BB43967312
Generated	2026-08-04

Product Overview

C22-DL-R-K01-24

Illuminated pushbutton actuator, Flat, momentary, 1 NC, Screw connection, LED Red, red, Blank, 24 V AC/DC, Bezel: titanium

Illuminated pushbutton actuator, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, Color LED: Red, button plate: red, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Illuminated pushbutton actuator, Flat, momentary, 1 NC, Screw connection, LED Red, red, Blank, 24 V AC/DC, Bezel: titanium
Illuminated pushbutton actuator, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, Colour LED: Red, button plate: red, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660
Delivery program
Product rangeRMQ CompactBasic functionIlluminated pushbutton actuatorsSingle unit/Complete unitComplete

unitDesignFlatmomentaryConnection typeScrew connectionColourLEDLEDRedButton platebutton plateredButton plateBlankRated operational voltage LED24 V AC/DCNameNoneDegree of ProtectionIP66, IP67, IP69Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/C = Normally closed1 NCNotes= safety function, by positive opening to IEC/EN 60947-5-1Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1[mm]4.65Maximum travel [mm]5.7Minimum force for positive opening [N]15Contact sequenceContact travel? = Contact closed? = Contact openContact diagramPositive opening (ZW)yesTechnical data
GeneralS...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DL-R-K01-24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.