

INDUSTRIAL COMPONENT DATA

C22-DL-W-K10-120 136627 EATON ELECTRIC Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Screw connec..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DL-W-K10-120



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DL-W-K10-120
Catalog number	136627
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-593E543911
Generated	2026-08-05

Product Overview

Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Screw connection, LED white, White, Blank, 120 V AC, Bezel: titanium

Illuminated pushbutton actuator, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, Color LED: white, button plate: White, Button plate Blank, Rated operational voltage LED: 120 V AC, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Illuminated pushbutton actuator, Flat, momentary, 1 N/O, Screw connection, LED white, White, Blank, 120 V AC, Bezel: titanium
Illuminated pushbutton actuator, RMQ Compact, Complete unit, Design: Flat, momentary, Connection type: Screw connection, Colour LED: white, button plate: White, Button plate Blank, Rated operational voltage LED: 120 V AC, Name: None, Degree of Protection: IP66, IP67, IP69K, Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660
Delivery program

Product rangeRMQ CompactBasic functionIlluminated pushbutton actuatorsSingle unit/Complete unitComplete unitDesignFlatmomentaryConnection typeScrew connectionColourLEDLEDwhiteButton platebutton plateWhiteButton plateBlankRated operational voltage LED120 V ACNameNoneDegree of ProtectionIP66, IP67, IP69Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open1 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data

General Standards IEC/EN 60947-5-1

VDE 0660 Lifespan, mechanical [Operations] > 5 x 10⁶ Operating frequency [Operations/h]? 3600 Actuating force? 5

n Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66, IP67, IP69 Ambient temperature Open-25 - +70 °C Ambient

temperature Storage- -30 - + 80 °C Mounting position As required Terminal capacities Solid 2 x 0.5 - 1.5_x mm² Terminal

capacities Flexible with ferrule 2 x 0.5 - 1.5_x mm² Tightening...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DL-W-K10-120 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.