

INDUSTRIAL COMPONENT DATA

C22-DR-R-K01-P1 185684 Y7-185684 EATON ELECTRIC Push button flush compact 22mm Latching Red 1 NC cable 0.2 m..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DR-R-K01-P1



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DR-R-K01-P1
Catalog number	Y7-185684
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-D6B82407C6
Generated	2026-08-05

Product Overview

Push button flush compact; 22mm; Latching; Red; 1 NC; cable 0.2 m and connector M12A

C22-DR-R-K01-P1

Pushbutton, classic, flat, maintained, 1 N/C, red, cable (black) with m12a plug, 4 pole, 0.2 m

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M12A plug, 4 pole, Cable Length: 0.2 m, button plate: red, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, classic, flat, maintained, 1 N/C, red, cable (black) with m12a plug, 4 pole, 0.2 mPushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M12A plug, 4 pole, Cable Length: 0.2 m, button plate: red, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

General specifications
Product name Eaton Moeller® series C22 Pushbutton
Part no. C22-DR-R-K01-P1
EAN 4015081811786
Product Length/Depth 260 millimetre
Product height 30 millimetre
Product width 30 millimetre
Product weight 0.035 kilogram
Certifications IEC/EN 60947-5-1
CSA
CE
VDE 0660
UL
CSA-C22.2 No. 14-18 and No. 94.2-15
UL File No.: E29184
UL Category Control No.: NKCR
UL 508
CE marking
CSA File No.: 165628
CSA Class No.: 321103
Product Tradename C22
Product Type Pushbutton
Product Sub Type None
Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1
Features & Functions Bezel color Titanium
Bezel material Plastic
Design M12A
Flat
Classical
Electric connection type Other
Features Positive opening
Fitted with: Front ring
Inscription Blank
General information Cabl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DR-R-K01-P1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.