

INDUSTRIAL COMPONENT DATA

C22-DR-R-K01-P62 185608 Y7-185608 EATON ELECTRIC Push button flush compact 22mm Latching Red 1 NC with free ..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DR-R-K01-P62



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DR-R-K01-P62
Catalog number	Y7-185608
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-1E56B0ED91
Generated	2026-08-05

Product Overview

Push button flush compact; 22mm; Latching; Red; 1 NC; with free cable 1 m

C22-DR-R-K01-P62

Eaton Moeller® series C22 Pushbutton, classic, flat, maintained, 1 N/C, red, cable (black) with non-terminated end, 4 pole, 1 m

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 1 m, button plate: red, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Pushbutton Catalog Number 185608 Model Code C22-DR-R-K01-P62 EAN 4015081811021 Product Length/Depth 1060 mm Product Height 30 mm Product Width 30 mm Product Weight 0.048 kg Certifications VDE 0660

CSA

IEC/EN 60947-5-1

UL
CE
CSA Class No.: 321103
CSA File No.: 165628
UL 508
CSA-C22.2 No. 14-18 and No. 94.2-15
CE marking
UL Category Control No.: NKCR
UL File No.: E29184 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions
Bezel color Titanium Bezel material Plastic Design Flat
Classical Electric connection type Cable Features Positive opening Fitted with: Front ring Inscription Blank General
Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection NEMA 12
IP67/IP69K Mounting position As required Opening diameter 22.5 mm Operating frequency 3600 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC
Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 2 Nm, Threaded ring Type Pushbutton actuator Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DR-R-K01-P62 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.