

INDUSTRIAL COMPONENT DATA

C22-DR-W-K10-P30 185704 EATON ELECTRIC Push button flush compact, 22 mm Interlocking White 1 NO cable 0.2 m ..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DR-W-K10-P30



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DR-W-K10-P30
Catalog number	185704
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-BA5CFD0DEE
Generated	2026-08-05

Product Overview

Push button flush compact, 22 mm; Interlocking; White; 1 NO; cable 0.2 m and connector M8

Pushbutton, classic, flat, maintained, 1 N/O, white, cable (black) with m8 plug, 4 pole, 0.2 m

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, button plate: White, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Pushbutton, classic, flat, maintained, 1 N/O, white, cable (black) with m8 plug, 4 pole, 0.2 m Pushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, button plate: White, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660 Delivery program

Product range RMQ compact solution Basic function Pushbutton actuators Single unit/Complete unit Complete unit Design Flat maintained Connection type Cable (black) with M8 plug, 4 pole Cable Length 0.2 m Button plate button plate White Button plate Blank Name None Degree of Protection IP66, IP67, IP69 (front) IP65 (on rear) Front ring Bezel: titanium Connection to SmartWire-DT no Contacts N/O = Normally open 1 N/O Contact sequence Contact travel? = Contact closed? = Contact open Contact diagram Technical data

General Standards IEC/EN 60947-5-1

VDE 0660 Certifications CE, UL, CSA Lifespan, mechanical [Operations] > 1 x 10⁶ Operating frequency [Operations/h]?

3600 Actuating force? 5 n Plug tightening torque 0.6 N/m Tightening torque Threaded ring 2 Nm Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66, IP67, IP69 (front)

IP65 (on rear) Ambient temperature Open-30 - +70 °C Ambient temperature Storage- 30 - + 80 °C Mounting position As required Mechanical shock resistance, shock dur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DR-W-K10-P30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.