

## INDUSTRIAL COMPONENT DATA

# C22-DRL-G-K10-24-P32 185582 EATON ELECTRIC

## Push-button light flush compact 22mm Latching Green 24 V AC/DC 1 ..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DRL-G-K10-24-P32



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | C22-DRL-G-K10-24-P32  |
| Catalog number  | 185582                |
| Category        | Push button, complete |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-AD2286D3CD         |
| Generated       | 2026-08-06            |

### Product Overview

Push-button light flush compact; 22mm; Latching; Green; 24 V AC/DC; 1 NO; cable 1 m and connector M8  
Illuminated pushbutton actuator, classic, flat, maintained, 1 N/O, green, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 1 m  
Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable  
(black) with M8 plug, 4 pole, Cable Length: 1 m, Color LED: green, button plate: green, Button plate Blank, Rated  
operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel:  
titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

Illuminated pushbutton actuator, classic, flat, maintained, 1 N/O, green, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 1 m  
Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable  
(black) with M8 plug, 4 pole, Cable Length: 1 m, Colour LED: green, button plate: green, Button plate Blank, Rated  
operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel:  
titanium, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660  
Delivery program

Product rangeRMQ compact solutionBasic functionIlluminated pushbutton actuatorsSingle unit/Complete unitComplete  
unitDesignFlatmaintainedConnection typeCable (black) with M8 plug, 4 poleCable Length1 mColourLEDLEDgreenButton

platebutton plategreenButton plateBlankRated operational voltage LED24 V AC/DCNameNoneDegree of ProtectionIP66, IP67, IP69 (front)  
IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open1 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data  
GeneralStandardsIEC/EN 60947-5-1  
VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]? 3600Actuating force? 5 nPlug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DRL-G-K10-24-P32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.