

INDUSTRIAL COMPONENT DATA

C22-DRL-R-K01-24-P32 185583 EATON ELECTRIC

Push-button light flush compact 22mm Latching Red 24 V AC/DC 1 NC..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-DRL-R-K01-24-P32



Manufacturer	EATON - MOELLER
MPN / Reference	C22-DRL-R-K01-24-P32
Catalog number	185583
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-38331E474B
Generated	2026-08-05

Product Overview

Push-button light flush compact; 22mm; Latching; Red; 24 V AC/DC; 1 NC; cable 1 m and connector M8

Illuminated pushbutton actuator, classic, flat, maintained, 1 N/C, red, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 1 m

Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Color LED: Red, button plate: red, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Illuminated pushbutton actuator, classic, flat, maintained, 1 N/C, red, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 1 m

Illuminated pushbutton actuator, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Colour LED: Red, button plate: red, Button plate Blank, Rated operational voltage LED: 24 V AC/DC, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive

opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660 Delivery program

Product range RMQ compact solution Basic function Illuminated pushbutton actuators Single unit/Complete unit Complete unit Design Flat maintained Connection type Cable (black) with M8 plug, 4 pole Cable Length 1 m Colour LED LED Red Button plate button plated Button plate Blank Rated operational voltage LED 24 V AC/DC Name None Degree of Protection IP66, IP67, IP69 (front)

IP65 (on rear) Front ring Bezel: titanium Connection to SmartWire-DT No Contacts N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 [mm] 4.65 Maximum travel [mm] 5.7 Minimum force for positive op...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-DRL-R-K01-24-P32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.