

INDUSTRIAL COMPONENT DATA

C22-L-G-24-P1 185120 Y7-185120 EATON ELECTRIC Indicator light, classic, flat, green, 24 V AC/DC, cable (blac..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-G-24-P1



Manufacturer	EATON - MOELLER
MPN / Reference	C22-L-G-24-P1
Catalog number	Y7-185120
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-B20307E1E8
Generated	2026-08-04

Product Overview

Indicator light, classic, flat, green, 24 V AC/DC, cable (black) with m12a plug, 4 pole, 0.2 m

C22-L-G-24-P1

Eaton Moeller® series C22 Indicator light, Flat, Cable (black) with M12A plug, 4 pole, 0.2 m, Lens green, LED green, 24 V AC/DC

Indicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M12A plug, 4 pole, Cable Length: 0.2 m, Color Lens: green, Color LED: green, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Indicator light Catalog Number 185120 Model Code C22-L-G-24-P1 EAN 4015081806027 Product Length/Depth 261 mm Product Height 30 mm Product Width 30 mm Product Weight 0.033 kg

Certifications UL

CE

VDE 0660

IEC/EN 60947-5-1

CSA Features & Functions

Bezel color Other Bezel material Plastic Design Flat
M12A Electric connection type Other Fitted with: Light source
Front ring Lens color Green Light color Green General
Cable length 0.2 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4 pole Degree of protection IP Other
NEMA Other Mounting position As required Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 1 Nm, Plug
2 Nm, Threaded ring Type Indicator lights Voltage type AC/DC Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Electrical rating
Rated conditional short-circuit current (Iq) 1 kA Rated insulation voltage (Ui) 30 V Rated operational voltage 24 V AC/DC (LED) Rated operational voltage (Ue) - min 24 V Rated operational voltage (Ue) - max 24 V Short-circuit protection rating Max. 4 A gG/gL, Fuse, Contacts Actuator
Actuator diame...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-G-24-P1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.