

INDUSTRIAL COMPONENT DATA

C22-L-R-24-P31 185131 EATON ELECTRIC Indicator light, classic, flat, red, 24 V AC/DC, cable (black) with m8 ..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-R-24-P31



Manufacturer	EATON - MOELLER
MPN / Reference	C22-L-R-24-P31
Catalog number	185131
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-7A2E68D240
Generated	2026-08-06

Product Overview

Indicator light, classic, flat, red, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 0.5 m

Indicator light compact, 22 mm; Red; 24 V AC/DC; with cable 0.5 m and connector M8

Indicator light, Flat, Cable (black) with M8 plug, 4 pole, 0.5 m, Lens Red, LED Red, 24 V AC/DC

Indicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.5 m, Color Lens: Red, Color LED: Red, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Indicator light, Flat, Cable (black) with M8 plug, 4 pole, 0.5 m, Lens Red, LED Red, 24 V AC/DCIndicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.5 m, Colour Lens: Red, Colour LED: Red, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660Delivery program

Product rangeRMQ compact solutionBasic functionIndicator lightsSingle unit/Complete unitComplete unitDesignFlatConnection typeCable (black) with M8 plug, 4 poleCable Length0.5 mColourLensRedLensLEDLEDRedRated operational voltage LED24 V AC/DCDegree of ProtectionIP66, IP67, IP69 (front) IP65 (on rear)Connection to SmartWire-DTnoContact sequenceTechnical data

General Standards IEC/EN 60947-5-1

VDE 0660 Certifications CE, UL, CSA Lifespan, mechanical [Operations] > 1 x 10⁶ Plug tightening torque 0.6 N/m Tightening torque Threaded ring 2 Nm Climatic proofing Damp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66, IP67, IP69 (front)
IP65 (on rear) Ambient temperature Open-30 - +70 °C Ambient temperature Storage- 30 - + 80 °C Mounting position As required
Mechanical shock resistance, shock duration 11 ms > 30 g Contacts Rated impulse withstand voltage [U_{imp}] 800 V AC
Rated insulation voltage [U_i] 30 V Overvoltage category/pollution degree III/3 Max. short-circuit protective device Fuse [gG/gL]...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-R-24-P31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.