

INDUSTRIAL COMPONENT DATA

C22-L-RGBYW-24-P72 197574 Y7-197574 EATON ELECTRIC

C22-L-RGBYW-24-P72

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-RGBYW-24-P72



Manufacturer	EATON - MOELLER
MPN / Reference	C22-L-RGBYW-24-P72
Catalog number	Y7-197574
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-05912A28F9
Generated	2026-08-06

Product Overview

C22-L-RGBYW-24-P72

Indicator light, Flush, Cable (black) with non-terminated end, 5-pole, 1 m, red/green/blue/yellow/white, 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Indicator light, Flush, Cable (black) with non-terminated end, 5-pole, 1 m, red/green/blue/yellow/white, 24 V DCDelivery program

Product rangeRMQ compact solutionBasic functionIndicator lightsMounting hole diameter [?]22.5 mmSingle unit/Complete unitComplete unitDesignFlushConnection typeCable (black) with non-terminated end, 5-poleCable Length1

mColourLenswhiteLensLEDLEDred/green/blue/yellow/whiteRated operational voltage LED24 V DCDegree of ProtectionIP66, IP67, IP69 (front)

IP65 (on rear)Connection to SmartWire-DTnoTechnical data

GeneralStandardsIEC/EN 60947-5-1

VDE 0660CertificationsCEClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69 (front)

IP65 (on rear)Ambient temperatureOpen-30 - +70 °CAmbient temperatureStorage- 30 - + 80 °CMounting positionAs

requiredMechanical shock resistance, shock duration 11 ms> 15 gContactsRated impulse withstand voltage [Uimp]800 V

ACRated insulation voltage [Ui]30 VOvervoltage category/pollution degreeIII/3Cable characteristicsDesignCable end

openCable Length1 mMaterial characteristicPURDiameter [?]4.7 mmPin assignmentFunctionFunctions (cable

BN/BU/BK/WH/GY):

OFF = 24 V DC/GND/0 V DC/0 V DC/0 V DC

GN = 24 V DC/GND/24 V DC/0 V DC/0 V DC

RD = 24 V DC/GND/0 V DC/24 V DC/0 V DC

YE = 24 V DC/GND/24 V DC/24 V DC/0 V DC

BU = 24 V DC/GND/0 V DC/0 V DC/24 V DC

WH = 24 V DC/GND/0 V DC/24 V DC/24 V DC

Green flashing = 24 V DC/GND/24 V DC/0 V DC/24 V DC

Red flashing = 24 V D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-RGBYW-24-P72 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.