

INDUSTRIAL COMPONENT DATA

C22-L-W-24-P31 185132 EATON ELECTRIC Indicator light, classic, flat, white, 24 V AC/DC, cable (black) with m..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-W-24-P31



Manufacturer	EATON - MOELLER
MPN / Reference	C22-L-W-24-P31
Catalog number	185132
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-8B23ECDBA3
Generated	2026-08-05

Product Overview

Indicator light, classic, flat, white, 24 V AC/DC, cable (black) with m8 plug, 4 pole, 0.5 m
Indicator light compact, 22 mm; White; 24 V AC/DC; with cable 0.5 m and connector M8
Indicator light, Flat, Cable (black) with M8 plug, 4 pole, 0.5 m, Lens white, LED white, 24 V AC/DC
Indicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.5 m, Color Lens: white, Color LED: white, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Indicator light, Flat, Cable (black) with M8 plug, 4 pole, 0.5 m, Lens white, LED white, 24 V AC/DCIndicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M8 plug, 4 pole, Cable Length: 0.5 m, Colour Lens: white, Colour LED: white, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660Delivery program

Product rangeRMQ compact solutionBasic functionIndicator lightsSingle unit/Complete unitComplete unitDesignFlatConnection typeCable (black) with M8 plug, 4 poleCable Length0.5

mColourLenswhiteLensLEDLEDwhiteRated operational voltage LED24 V AC/DCDegree of ProtectionIP66, IP67, IP69 (front)

IP65 (on rear)Connection to SmartWire-DTnoContact sequenceTechnical data
GeneralStandardsIEC/EN 60947-5-1
VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Plug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66, IP67, IP69 (front)
IP65 (on rear)Ambient temperatureOpen-30 - +70 °CAmbient temperatureStorage- 30 - + 80 °CMounting positionAs requiredMechanical shock resistance, shock duration 11 ms> 30 gContactsRated impulse withstand voltage [Uimp]800 V
ACRated insulation voltage [Ui]30 VOvervoltage category/pollution degreeIII/3Max. short-circuit protective device...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-W-24-P31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.