

INDUSTRIAL COMPONENT DATA

**C22-L-XB-120 121643 Y7-121643 EATON ELECTRIC
C22-L-XB-120**

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-XB-120



Manufacturer	EATON - MOELLER
MPN / Reference	C22-L-XB-120
Catalog number	Y7-121643
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-C858C9C34C
Generated	2026-08-05

Product Overview

C22-L-XB-120

Eaton Moeller® series C22 Indicator light, Flat, Screw connection, Lens Without lens, LED Blue, 120 V AC
Indicator light, Product range: RMQ Compact, Complete unit, Design: Flat, Connection type: Screw connection, Color Lens:
Without lens, Color LED: Blue, Rated operational voltage LED: 120 V AC, Degree of Protection: IP66, IP67, IP69K,
Connection to SmartWire-DT: no, Ordering information: Lenses for indicator lights -> accessories, Standards: IEC/EN
60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Indicator light Catalog Number 121643 Model Code C22-L-XB-120 EAN
4015081194575 Product Length/Depth 56 mm Product Height 30 mm Product Width 30 mm Product Weight 0.015 kg

Certifications CE marking

CSA File No.: 165628

CSA Class No.: 321103

UL 508

VDE 0660

UL Listed

UL File No.: E29184

IEC/EN 60947-5-1

CSA-C22.2 No. 14-05 and 94-M91

CSA certified

UL Category Control No.: NKCR Catalog Notes Lenses for indicator lights -> accessories Features & Functions

Bezel color Other Bezel material Plastic Design Flat Electric connection type Screw connection Fitted with: Front ring

Light source Lens color Without hood Light color Blue General

Connection to SmartWire-DT No Degree of protection NEMA 4X, 13

IP67/IP69K Mounting position As required Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product

Category RMQ Compact Rated impulse withstand voltage (Uimp) 4000 V AC Terminal capacity 2 x (0.5 - 1.5) mm², solid

2 x (0.5 - 1.5) mm², flexible with ferrules to DIN 46228 Tightening torque 0.8 Nm, Screw terminals Type Indicator lights

Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated insulation voltage (Ui) 250 V Rated operational voltage (Ue) - min 120 V Rated o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-XB-120 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.