

## INDUSTRIAL COMPONENT DATA

# C22-L-XB-24 121634 Y7-121634 EATON ELECTRIC

## C22-L-XB-24

Brand: EATON - MOELLER | Manufacturer Part Number: C22-L-XB-24



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | C22-L-XB-24              |
| Catalog number  | Y7-121634                |
| Category        | Indicator light complete |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-C5BD1E95C2            |
| Generated       | 2026-08-05               |

### Product Overview

C22-L-XB-24

Eaton Moeller® series C22 Indicator light, Flat, Screw connection, Lens Without lens, LED Blue, 24 V AC/DC  
Indicator light, Product range: RMQ Compact, Complete unit, Design: Flat, Connection type: Screw connection, Color Lens:  
Without lens, Color LED: Blue, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K,  
Connection to SmartWire-DT: no, Ordering information: Lenses for indicator lights -> accessories, Standards: IEC/EN  
60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series C22 Indicator light Catalog Number 121634 Model Code C22-L-XB-24 EAN  
4015081194483 Product Length/Depth 56 mm Product Height 30 mm Product Width 30 mm Product Weight 0.015 kg  
Certifications CSA File No.: 165628  
CSA-C22.2 No. 14-05 and 94-M91  
UL Category Control No.: NKCR  
UL 508  
VDE 0660  
CSA Class No.: 321103  
CE marking

UL Listed

IEC/EN 60947-5-1

UL File No.: E29184

CSA certified Catalog Notes Lenses for indicator lights -> accessories Features & Functions

Bezel color Other Bezel material Plastic Design Flat Electric connection type Screw connection Fitted with: Light source

Front ring Lens color Without hood Light color Blue General

Connection to SmartWire-DT No Degree of protection NEMA 4X, 13

IP67/IP69K Mounting position As required Opening diameter 22.5 mm Overvoltage category III Pollution degree 3 Product

Category RMQ Compact Rated impulse withstand voltage (Uimp) 4000 V AC Terminal capacity 2 x (0.5 - 1.5) mm<sup>2</sup>, flexible with ferrules to DIN 46228

2 x (0.5 - 1.5) mm<sup>2</sup>, solid Tightening torque 0.8 Nm, Screw terminals Type Indicator lights Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated insulation voltage (Ui) 250 V Rated operational voltage 24 V AC/DC (LED) Rated...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-L-XB-24 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.