

INDUSTRIAL COMPONENT DATA

C22-PV-K02-P1 182975 EATON ELECTRIC Compact emergency stop button. 22 mm. D 45mm

Brand: EATON - MOELLER | Manufacturer Part Number: C22-PV-K02-P1



Manufacturer	EATON - MOELLER
MPN / Reference	C22-PV-K02-P1
Catalog number	Y7-182975
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-922D623CE9
Generated	2026-08-05

Product Overview

Compact emergency stop button. 22 mm. D=45mm

Emergency stop/emergency switching off button, classic, mushroom, 38mm, pull release, 2 N/C, cable (black) with m12a plug, 4p, 0.2m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton Catalog Number 182975
Model Code C22-PV-K02-P1 EAN 4015081779024 Product Length/Depth 297 mm Product Height 38 mm Product Width 38 mm Product Weight 0.051 kg Certifications IEC/EN 60947-5-1

CSA

CSA-C22.2 No. 14-10

CSA Class No.: 321103

UL

IEC/EN 60947-5-5

CSA certified

CSA File No.: 165628

CSA-C22.2 No. 94-91

UL Listed

UL File No.: E340491

CE

UL 508

VDE 0660

CE marking

CSA-C22.2 No. 94.2-07 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Base color Yellow Design Classical

Mushroom-shaped

M12A Features Tamper-proof (according to ISO 13850, EN 418)

Positive opening Illumination Non-illuminated Unlocking method Pull-release General

Cable length 0.2 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4 pole Degree of protection IP Other

NEMA 4X, 13 Lifespan, mechanical 50,000 operations Mounting method Built-in Mounting position As required Opening

diameter 22.5 mm Operating frequency 300 Operations/h Overvoltage category III Pollution degree 3 Product category

RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock

duration 11 ms Tightening torque 2 Nm, Threaded ring

1 Nm, Plug Type Controlled stop pushbutton/emergency-stop button Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-PV-K02-P1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.