

INDUSTRIAL COMPONENT DATA

C22-PVS45P-MS1-K02 121619 EATON ELECTRIC

Emergency-stop, 45mm, MS1, 2N/C, red

Brand: EATON - MOELLER | Manufacturer Part Number: C22-PVS45P-MS1-K02



Manufacturer	EATON - MOELLER
MPN / Reference	C22-PVS45P-MS1-K02
Catalog number	121619
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-F906FAC1AB
Generated	2026-08-04

Product Overview

Emergency-stop, 45mm, MS1, 2N/C, red

C22-PVS45P-MS1-K02

Emergency-stop, Palm-tree shape, 45 mm, Key-release, MS1, 2 NC, Screw connection, Not suitable for master key systems

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Emergency-stop, Palm-tree shape, 45 mm, Key-release, MS1, 2 NC, Screw connection, Not suitable for master key systems

Emergency-stop, Product range: RMQ Compact, Complete unit, Design: Palm-tree shape, Diameter: 45 mm, Illumination: Non-illuminated, Key-release, Connection type: Screw connection, Description: Tamper-proof according to ISO 13850/EN 418, Lock mechanism: MS1, Colour Mushroom head: Red, Colour Base: yellow, Degree of Protection: IP66, IP67, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 2 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 30, Information about equipment supplied: 1 key included as standard, Standards: IEC/EN 60947-5-5, VDE 0660 Delivery program

Product range RMQ Compact Basic function Controlled stop pushbuttons/emergency-stop buttons Single unit/Complete unit Complete unit Design Palm-tree shape Diameter [?] 45 mm Illumination Non-illuminated Approval Key-release Connection type Screw connection Description Tamper-proof according to ISO 13850/EN 418 Not suitable for master key systems Lock mechanism MS1 Colour Mushroom head Red Base yellow Degree of Protection IP66, IP67, IP69 Connection to

SmartWire-DT no Contacts N/C = Normally closed 2 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1
Actuator travel and actuation force as per DIN EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-PVS45P-MS1-K02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.