

INDUSTRIAL COMPONENT DATA

C22-PVT-K02-P10 191005 Y7-191005 EATON ELECTRIC

Controlled stop/emergency stop button, classic, mushroom, 38..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-PVT-K02-P10



Manufacturer	EATON - MOELLER
MPN / Reference	C22-PVT-K02-P10
Catalog number	Y7-191005
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-3D81E58813
Generated	2026-08-06

Product Overview

Controlled stop/emergency stop button, classic, mushroom, 38mm, turn-to-release function, 2 N/C, cable (black) with m12a plug, 4 pole, 0.2m

C22-PVT-K02-P10

Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton, Mushroom-shaped, 38 mm, Turn-to-release function, 2 NC, Cable (black) with M12A plug, 5 pole, 0.2 m

Controlled stop/emergency stop button, range: RMQ compact solution, complete device, design: mushroom-shaped, diameter: 38 mm, lighting: non-illuminated, turn-to release function, connection type: Cable (black) with M12A plug, 5-pole, cable length: 0.2 m, description: tamper-proof in accordance with ISO 13850, EN 418, color of mushroom head: red, color of base: yellow, degree of protection: IP66, IP67, IP69K (on front), IP65 (on rear), connection to SmartWire-DT: no, Contact configuration N/C: 2, contact configuration Special note: = safety function, by positive opening to IEC/EN 60947-5-1 , sequence of the control panel and actuating force in accordance with DIN EN 60947-5-1, K.5.4.1 positive opening sequence: mm 4.65, maximum sequence: mm 5.7, minimum force for positive opening: N 30, standards: IEC/EN 60947-5-5, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Emergency stop/emergency switching off pushbutton Catalog Number 191005
Model Code C22-PVT-K02-P10 EAN 4015081912261 Product Length/Depth 297 mm Product Height 38 mm Product Width 38 mm Product Weight 0.061 kg Certifications CE

UL

IEC/EN 60947-5-5

VDE 0660

CSA

CSA Class No.: 321103

CSA File No.: 165628

IEC/EN 60947-5-1

UL 508

CSA-C22.2 No. 14-10

CSA-C22.2 No. 94-91

CSA-C22.2 No. 94.2-07

CE marking

UL File No.: E340491 Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Base color Yellow Design Mushroom-shaped

M12A

Classical Features Tamper-proof (according to ISO 13850, EN 418)

Positive opening Illumination Non-illuminated Unlocking method Turn-release General

Cable length 0.2 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 5 pole Degree of protection IP Other

NEMA 4X, 13 Lifespan, mechanical 50,000 operations Mounting method Built-in Mounting position As required Opening diameter 22.5 mm Operating frequency 300 Operations/h Overvoltage category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 1 Nm, Plug

2 Nm, Threaded ring Type Controlled stop pushbutton/emergency-stop button Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-PVT-K02-P10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.