

INDUSTRIAL COMPONENT DATA

C22-PVT-K11-P65 185182 Y7-185182 EATON ELECTRIC

Emergency stop/emerg. switching off button, classic,palm-tre..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-PVT-K11-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-PVT-K11-P65
Catalog number	Y7-185182
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-E88353D61D
Generated	2026-08-06

Product Overview

Emergency stop/emerg. switching off button, classic,palm-tree,38mm,turn-to-release function, N/C,1 N/O,cable (black) with non-terminated end,4p,3.5m

C22-PVT-K11-P65

Emergency stop/emergency switching off pushbutton, Mushroom-shaped, 38 mm, Turn-to-release function, 1 NC, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m

Emergency stop/emergency switching off pushbutton, Product range: RMQ compact solution, Complete unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Turn-to-release function, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, Description: Tamper-proof according to ISO 13850, EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1 , Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-5, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Emergency stop/emergency switching off pushbutton, Mushroom-shaped, 38 mm, Turn-to-release function, 1 NC, 1 N/O,

Cable (black) with non-terminated end, 4 pole, 3.5 mEmergency stop/emergency switching off pushbutton, Product range: RMQ compact solution, Complete unit, Design: Mushroom-shaped, Diameter: 38 mm, Illumination: Non-illuminated, Turn-to-release function, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, Description: Tamper-proof according to ISO 13850, EN 418, Color Mushroom head: Red, Color Base: yellow, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts N/O = Normally open: 1 N/O, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1 , Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 20, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-5, VDE 0660

General specificationsProduct nameEaton Moeller® series C22 Emergency stop/emergency switching off pushbuttonPart no.C22-PVT-K11-P65EAN4015081806676Product Length/Depth3597 millimetreProduct height38 millimetreProduct width38 millimetreProduct weight0.151 kilogramCertificationsCSA

CE

VDE 0660

IEC/EN 60947-5-5

UL

CSA File No.: 165628

CSA-C22.2 No. 14-10

CSA-C22.2 No. 94.2-07

UL 508

UL File No.: E340491

CE marking

IEC/EN 60947-5-1

CSA Class No.: 321103

CSA-C22.2 No. 94-91Product....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-PVT-K11-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.