

INDUSTRIAL COMPONENT DATA

C22-PVT45P-K02 121611 Y7-121611 EATON ELECTRIC

Emergency-stop, 45mm, pull/turn release, 2N/C, black

Brand: EATON - MOELLER | Manufacturer Part Number: C22-PVT45P-K02



Manufacturer	EATON - MOELLER
MPN / Reference	C22-PVT45P-K02
Catalog number	Y7-121611
Category	Emergency stop complete
Minimum order	1 Pcs
Document ID	EO-51FAC9597B
Generated	2026-08-04

Product Overview

Emergency-stop, 45mm, pull/turn release, 2N/C, black

C22-PVT45P-K02

Eaton Moeller® series C22 Emergency-stop, Palm-tree shape, 45 mm, Turn-to-release function, 2 NC, Screw connection
Emergency-stop, Product range: RMQ Compact, Complete unit, Design: Palm-tree shape, Diameter: 45 mm, Illumination:
Non-illuminated, Turn-to-release function, Connection type: Screw connection, Description: Tamper-proof according to ISO
13850/EN 418, Color Mushroom head: Red, Color Base: yellow, Red mushroom head (RAL 3000), Degree of Protection:
IP66, IP67, IP69K, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 2 NC, Contacts Notes: = safety
function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1:
mm 4.65, Maximum travel: mm 5.7 , Minimum force for positive opening: N 30, Function: Turn-to-release function,
Standards: IEC/EN 60947-5-5, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Emergency-stop button Catalog Number 121611 Model Code C22-PVT45P-K02

EAN 4015081194292 Product Length/Depth 95 mm Product Height 45 mm Product Width 45 mm Product Weight 0.055 kg

Certifications CE Features & Functions

Unlocking method Turn-release General

Degree of protection IP67/IP69K

NEMA 4X, 13 Mounting method Built-in Mounting position As required Opening diameter 22.5 mm Electrical rating

Rated insulation voltage (Ui) 250 V Contacts

Number of contacts (normally closed contacts) 2 Number of contacts (normally open contacts) 0

ETIM for 121611 Low-voltage industrial controls and switchgear (EC002034)

Feature Name

Feature Value

Unlocking method (EF001403)

Turn-release

Number of contacts as normally closed contact (EF008255)

2

Number of contacts as normally open contact (EF008256)

0

Degree of protection (IP) (EF005474)

IP67/IP69K

Degree of protection (NEMA) (EF011959)

4X, 13

Mounting method (EF000003)

Built-in

With lighting (EF003829)

No

Supply voltage lamp (EF006522)

0 V

Hole diameter (EF000079)

22.5 mm

Connection type auxiliary circuit (EF006820)

Other

Diameter cap (EF001423)

45 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-PVT45P-K02 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.