

## INDUSTRIAL COMPONENT DATA

# C22-WK-K10-P30 186130 EATON ELECTRIC Changeover selector switch, classic, with thumb-grip, momentary, 2 posi..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WK-K10-P30



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | C22-WK-K10-P30            |
| Catalog number  | 186130                    |
| Category        | Selector switch, complete |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-01635378EA             |
| Generated       | 2026-08-05                |

## Product Overview

Changeover selector switch, classic, with thumb-grip, momentary, 2 positions, 1 N/O, cable (black) with m8 plug, 4 pole, 0.2 m

Selector Lever short, compact; Return; 2 positions; 1 NO; cable 0.2 m and connector M8

Changeover switch, With thumb-grip, momentary, 1 N/O, Cable (black) with M8 plug, 4 pole, 0.2 m, 2 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, momentary, Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, 2 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

Changeover switch, With thumb-grip, momentary, 1 N/O, Cable (black) with M8 plug, 4 pole, 0.2 m, 2 positions, Bezel: titaniumChangeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, momentary, Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, 2 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)Delivery program

Product rangeRMQ compact solutionBasic functionSelector switch actuatorsSingle unit/Complete unitComplete unitDesignWith thumb-gripmomentaryFunction: [= spring-return]40°Connection typeCable (black) with M8 plug, 4 poleCable

Length 0.2 m 2 positions Degree of Protection IP66 (front)  
IP65 (on rear) Front ring Bezel: titanium Connection to SmartWire-DT no Contacts N/O = Normally open 1 N/O Contact  
sequence Contact travel? = Contact closed? = Contact open Contact diagram Technical data  
General Standards IEC/EN 60947-5-1  
VDE 0660 Certifications CE, UL, CSA Lifespan, mechanical [Operations] > 1 x 10<sup>6</sup> Operating frequency [Operations/h]?  
2000 Operating torque? 0.3 Nm Plug tightening torque 0.6 N/m Tightening torque Threaded ring 2 Nm Climatic proofing Damp  
heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66 (front)  
IP65 (on rear) Ambient temperature Open -30 - +70 °C Ambient temperature Storage -30 - +80 °C Mounting position As  
required Mechanical shock resistance, shock dura...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WK-K10-P30 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.