

INDUSTRIAL COMPONENT DATA

C22-WK3-K20-P32 186154 EATON ELECTRIC Changeover selector switch, classic, with thumb-grip, momentary, 3 pos..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WK3-K20-P32



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WK3-K20-P32
Catalog number	186154
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-8BF464859F
Generated	2026-08-05

Product Overview

Changeover selector switch, classic, with thumb-grip, momentary, 3 positions, 2 N/O, cable (black) with M8 plug, 4 pole, 1.0 m

Selector Lever short, compact; Return; 3 positions; 2; with cable 1 m and connector M8

Changeover switch, With thumb-grip, momentary, 2 N/O, Cable (black) with M8 plug, 4 pole, 1 m, 3 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, momentary, Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, 3 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Changeover switch, With thumb-grip, momentary, 2 N/O, Cable (black) with M8 plug, 4 pole, 1 m, 3 positions, Bezel: titaniumChangeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, momentary, Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, 3 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)Delivery program

Product rangeRMQ compact solutionBasic functionSelector switch actuatorsSingle unit/Complete unitComplete unitDesignWith thumb-gripmomentaryFunction: [= spring-return]40°40°Connection typeCable (black) with M8 plug, 4

poleCable Length1 m3 positionsDegree of ProtectionIP66 (front)
IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open2 N/OContact
sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data
GeneralStandardsIEC/EN 60947-5-1
VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]?
2000Operating torque? 0.3 NmPlug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp
heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66 (front)
IP65 (on rear)Ambient temperatureOpen-30 - +70 °CAmbient temperatureStorage- 30 - + 80 °CMounting positionAs
requiredMechanical shock resistance, shock duratio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WK3-K20-P32 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.