

INDUSTRIAL COMPONENT DATA

C22-WK3-K20-P5 186122 Y7-186122 EATON ELECTRIC

Changeover selector switch, classic, with thumb-grip, momenta..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WK3-K20-P5



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WK3-K20-P5
Catalog number	Y7-186122
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-2295E64E5A
Generated	2026-08-04

Product Overview

Changeover selector switch, classic, with thumb-grip, momentary, 3 positions, 2 N/O, cable (black) with M12A plug, 4 pole, 1.0 m

C22-WK3-K20-P5

Eaton Moeller® series C22 Changeover switch, With thumb-grip, momentary, 2 N/O, Cable (black) with M12A plug, 4 pole, 1 m, 3 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, momentary, Cable (black) with M12A plug, 4 pole, Cable Length: 1 m, 3 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Changeover switch Catalog Number 186122 Model Code C22-WK3-K20-P5
EAN 4015081816231 Product Length/Depth 1076 mm Product Height 30 mm Product Width 30 mm Product Weight 0.059 kg
Certifications CE
IEC/EN 60947-5-1

UL
VDE 0660
CSA
CSA File No.: 165628
CSA Class No.: 321103
UL File No.: E29184
UL 508
CSA-C22.2 No. 14-18 and No. 94.2-15
CE marking
UL Category Control No.: NKCR
UL listed, CSA certified Features & Functions
Bezel color Titanium Bezel material Plastic Design With thumb-grip
M12A
Classical Electric connection type Other Fitted with: Front ring General
Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4 pole Degree of protection IP66
IP65, rear
NEMA Other Lifespan, mechanical 1,000,000 Operations (AC operated) Mounting position As required Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Switching angle 40 ° Tightening torque 2 Nm, Threaded ring 1 Nm, Plug Type Selector switch actuator Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp heat, constant, to IEC 60068-2-78 Electrical rating
Rated conditi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WK3-K20-P5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.