

INDUSTRIAL COMPONENT DATA

C22-WRK-K01-P65 186182 Y7-186182 EATON ELECTRIC

Changeover switch, classic, with thumb-grip, maintained, 2 p..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRK-K01-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRK-K01-P65
Catalog number	Y7-186182
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-F3B1ACA5D1
Generated	2026-08-05

Product Overview

Changeover switch, classic, with thumb-grip, maintained, 2 positions, 1 N/C, cable (black) with non-terminated end, 4 pole, 3.5 m

C22-WRK-K01-P65

Eaton Moeller® series C22 Changeover switch, With thumb-grip, maintained, 1 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, maintained, Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, 2 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, 1 NC, = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 Maximum travel: mm 5.7, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 Minimum force for positive opening: N 15 , Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Changeover switch Catalog Number 186182 Model Code C22-WRK-K01-P65
EAN 4015081816835 Product Length/Depth 3576 mm Product Height 30 mm Product Width 30 mm Product Weight 0.122 kg
Certifications CE

UL
IEC/EN 60947-5-1
VDE 0660
CSA
CSA File No.: 165628
CSA Class No.: 321103
UL File No.: E29184
UL 508
CSA-C22.2 No. 14-18 and No. 94.2-15
CE marking
UL Category Control No.: NKCR
UL listed, CSA certified Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions
Bezel color Titanium Bezel material Plastic Design With thumb-grip
Cable end open
Classical Electric connection type Other Features Positive opening Fitted with: Front ring General
Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection IP66
IP65, rear
NEMA Other Mounting position As required Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Switching angle 60 °
Tightening torque 2 Nm, Threaded ring Type Selector switch actuator Climatic environmental conditions
Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30
Damp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRK-K01-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.