

INDUSTRIAL COMPONENT DATA

C22-WRK-K10-P65 186183 Y7-186183 EATON ELECTRIC

Changeover switch, classic, with thumb-grip, maintained, 2 p..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRK-K10-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRK-K10-P65
Catalog number	Y7-186183
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-B56994C384
Generated	2026-08-05

Product Overview

Changeover switch, classic, with thumb-grip, maintained, 2 positions, 1 N/O, cable (black) with non-terminated end, 4 pole, 3.5 m

C22-WRK-K10-P65

Eaton Moeller® series C22 Changeover switch, With thumb-grip, maintained, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, maintained, Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, 2 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Changeover switch Catalog Number 186183 Model Code C22-WRK-K10-P65

EAN 4015081816842 Product Length/Depth 3576 mm Product Height 30 mm Product Width 30 mm Product Weight 0.122 kg Certifications VDE 0660

CE

IEC/EN 60947-5-1

UL

CSA

CSA File No.: 165628

CSA Class No.: 321103

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL listed, CSA certified Features & Functions

Bezel color Titanium Bezel material Plastic Design With thumb-grip

Cable end open

Classical Electric connection type Other Fitted with: Front ring General

Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection IP66

IP65, rear

NEMA Other Mounting position As required Opening diameter 22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Switching angle 60 °

Tightening torque 2 Nm, Threaded ring Type Selector switch actuator Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRK-K10-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.