

INDUSTRIAL COMPONENT DATA

C22-WRK-K20 132531 EATON ELECTRIC C22-WRK-K20

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRK-K20



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRK-K20
Catalog number	132531
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-C310A05ED4
Generated	2026-08-04

Product Overview

C22-WRK-K20

Changeover switch, With thumb-grip, maintained, 2 N/O, Screw connection, 2 positions, Bezel: titanium

Changeover switch, Product range: RMQ Compact, Complete unit, Design: With thumb-grip, maintained, Screw connection, 2 positions, Degree of Protection: IP65, Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP65

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Changeover switch, With thumb-grip, maintained, 2 N/O, Screw connection, 2 positions, Bezel: titaniumChangeover switch, Product range: RMQ Compact, Complete unit, Design: With thumb-grip, maintained, Screw connection, 2 positions, Degree of Protection: IP65, Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP65Delivery program

Product rangeRMQ CompactBasic functionSelector switch actuatorsSingle unit/Complete unitComplete unitDesignWith thumb-gripmaintainedFunction: [= spring-return]60°Connection typeScrew connection2 positionsDegree of ProtectionIP65Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open2 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramTechnical data

GeneralStandardsIEC/EN 60947-5-1

VDE 0660Lifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]? 2000Operating torque? 0.3

NmClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP65Mounting positionAs requiredTerminal capacitiesSolid2 x 0.5

- 1.5 mm² Terminal capacities Flexible with ferrule 2 x 0.5 - 1.5 mm² Tightening torque for terminal screw 0.8 Nm
Contacts Rated impulse withstand voltage [U_{imp}] 4000 V AC Rated insulation voltage [U_i] 250 V Rated conditional short-circuit current [I_q] 1 kA Overvoltage category/pollution degree III/3 Control circuit reliability at 24 V DC/5 mA [HF] values follow Fault probability Control circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRK-K20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.