

INDUSTRIAL COMPONENT DATA

C22-WRK3-K20-P5 186125 Y7-186125 EATON ELECTRIC

Changeover switch, classic, with thumb-grip, maintained, 3 p..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRK3-K20-P5



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRK3-K20-P5
Catalog number	Y7-186125
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-053C008620
Generated	2026-08-06

Product Overview

Changeover switch, classic, with thumb-grip, maintained, 3 positions, 2 N/O, cable (black) with M12A plug, 4 pole, 1 m
C22-WRK3-K20-P5

Eaton Moeller® series C22 Changeover switch, With thumb-grip, maintained, 2 N/O, Cable (black) with M12A plug, 4 pole, 1 m, 3 positions, Bezel: titanium

Changeover switch, Product range: RMQ compact solution, Complete unit, Design: With thumb-grip, maintained, Cable (black) with M12A plug, 4 pole, Cable Length: 1 m, 3 positions, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Changeover switch Catalog Number 186125 Model Code C22-WRK3-K20-P5
EAN 4015081816262 Product Length/Depth 1076 mm Product Height 30 mm Product Width 30 mm Product Weight 0.059 kg
Certifications CE
CSA
UL
VDE 0660
IEC/EN 60947-5-1

CSA File No.: 165628

CSA Class No.: 321103

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL listed, CSA certified Features & Functions

Bezel color Titanium Bezel material Plastic Design M12A

With thumb-grip

Classical Electric connection type Other Fitted with: Front ring General

Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4

pole Degree of protection IP65, rear

IP66

NEMA Other Lifespan, mechanical 1,000,000 Operations (AC operated) Mounting position As required Opening diameter

22.5 mm Operating frequency 2000 Operations/h Operating torque 0.3 Nm Overvoltage category III Pollution degree 3

Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g,

Mechanical, Shock duration 11 ms Switching angle 60 ° Tightening torque 2 Nm, Threaded ring

1 Nm, Plug Type Selector switch actuator Climatic environmental conditions

Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated condit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRK3-K20-P5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.