

INDUSTRIAL COMPONENT DATA

C22-WRS-MS1-A1-K10 132873 EATON ELECTRIC

C22-WRS-MS1-A1-K10

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRS-MS1-A1-K10



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRS-MS1-A1-K10
Catalog number	132873
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-7E67C09D54
Generated	2026-08-05

Product Overview

C22-WRS-MS1-A1-K10

Key-operated actuator, RMQ Compact, maintained, 1 N/O, Screw connection, 2 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ Compact, Complete unit, maintained, Screw connection, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, RMQ Compact, maintained, 1 N/O, Screw connection, 2 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ Compact, Complete unit, maintained, Screw connection, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66

Delivery program

Product range RMQ Compact

Basic function Key-operated buttons

Single unit/Complete unit Complete unit

maintained

Function: [= spring-return] 60°

Connection type Screw connection

Not suitable for master key systems

2 positions

Lock mechanism MS1

Key withdrawable in position 0

Degree of Protection IP66

Front ring Bezel: titanium

Connection to SmartWire-DT no

Contacts N/O = Normally open

1 N/O

Contact sequence Contact travel? = Contact closed? = Contact open

Contact diagram

Information about equipment supplied With 1 key

Technical data

General

Standards IEC/EN 60947-5-1

VDE 0660

Lifespan, mechanical [Operations] > 0.1 x 10⁶

Operating frequency [Operations/h] ? 100

Operating torque ? 0.5

NmClimatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Degree of ProtectionIP66Mounting positionAs requiredTerminal capacitiesSolid2 x 0.5
- 1.5 mm²Terminal capacitiesFlexible with ferrule2 x 0.5 - 1.5 mm²Tightening torque for terminal screw0.8
NmContactsRated impulse withstand voltage [Uimp]4000 V ACRated insulation voltage [Ui]250 VRated conditional
short-ci...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRS-MS1-A1-K10 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.