

## INDUSTRIAL COMPONENT DATA

# C22-WRS-MS1-K01-P65 186278 Y7-186278 EATON ELECTRIC

## Key-operated actuator, classic, maintained, 2 positions,..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRS-MS1-K01-P65



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | C22-WRS-MS1-K01-P65       |
| Catalog number  | Y7-186278                 |
| Category        | Selector switch, complete |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-0E7FA9BDAF             |
| Generated       | 2026-08-05                |

### Product Overview

Key-operated actuator, classic, maintained, 2 positions, MS1, 1 N/C, cable (black) with non-terminated end, 4 pole, 3.5 m  
C22-WRS-MS1-K01-P65

Eaton Moeller® series C22 Key-operated actuator, RMQ compact solution, maintained, 1 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, 2 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, I, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, 1 NC, = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 Maximum travel: mm 5.7, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1 Minimum force for positive opening: N 15, Positive opening (ZW): yes, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series C22 Key-operated actuator Catalog Number 186278 Model Code

C22-WRS-MS1-K01-P65 EAN 4015081817795 Product Length/Depth 3597 mm Product Height 30 mm Product Width 30 mm Product Weight 0.143 kg Certifications CSA

IEC/EN 60947-5-1

UL  
CE  
VDE 0660  
CSA File No.: 165628  
CSA Class No.: 321103  
UL File No.: E29184  
UL 508  
CSA-C22.2 No. 14-18 and No. 94.2-15  
CE marking  
UL Category Control No.: NKCR  
UL listed, CSA certified Features & Functions  
Bezel color Titanium Bezel material Plastic Design Cable end open  
Classical Electric connection type Other Features Positive opening Fitted with: Front ring Key code MS1 General  
Accessories 1 key included with supplied equipment. Cable length 3.5 m Cable material PUR Connection to SmartWire-DT  
No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection IP65, rear  
IP66  
NEMA Other Mounting position As required Opening diameter 22.5 mm Operating frequency 100 Operations/h Operating  
torque 0.5 Nm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse  
withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Switching angle 60 °  
Tightening torque 2 Nm, Threaded ring Type Key-operated button Climatic environmental conditions  
Ambient operating temperature - min -30 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat,  
cyclic, to IEC 60068-2-30  
Damp heat, constant, to IEC 60068-2-78...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRS-MS1-K01-P65 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.