

## INDUSTRIAL COMPONENT DATA

# C22-WRS-MS1-K10-P30 186231 EATON ELECTRIC

## Key-operated actuator, classic, maintained, 2 positions, MS1, 1 N/..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRS-MS1-K10-P30



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | C22-WRS-MS1-K10-P30       |
| Catalog number  | 186231                    |
| Category        | Selector switch, complete |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-911788DA89             |
| Generated       | 2026-08-05                |

### Product Overview

Key-operated actuator, classic, maintained, 2 positions, MS1, 1 N/O, cable (black) with m8 plug, 4 pole, 0.2 m

Key Selector compact; Interlocking; 2 positions; Key: MS1; 1 NO; cable 0.2 m and connector M8

Key-operated actuator, RMQ compact solution, maintained, 1 N/O, Cable (black) with M8 plug, 4 pole, 0.2 m, 2 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, I, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

### Additional Product Information

Key-operated actuator, RMQ compact solution, maintained, 1 N/O, Cable (black) with M8 plug, 4 pole, 0.2 m, 2 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with M8 plug, 4 pole, Cable Length: 0.2 m, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, I, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear) Delivery program Product range RMQ compact solution Basic function Key-operated buttons Single unit/Complete unit Complete

unitmaintainedFunction: [= spring-return]60°Connection typeCable (black) with M8 plug, 4 poleCable Length0.2 mNot suitable for master key systems2 positionsLock mechanismMS1Key withdrawable in positionI0Degree of ProtectionIP66 (front)  
IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open1 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramInformation about equipment suppliedWith 1 keyTechnical data  
GeneralStandardsIEC/EN 60947-5-1  
VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]? 100Operating torque? 0.5 NmPlug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30Degree of Protectio...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRS-MS1-K10-P30 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.