

INDUSTRIAL COMPONENT DATA

C22-WRS3-MS1-K20-P32 186253 EATON ELECTRIC

Key-operated actuator, classic, maintained, 3 positions, MS1, 2 N..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRS3-MS1-K20-P32



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRS3-MS1-K20-P32
Catalog number	186253
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-6A4F12A650
Generated	2026-08-05

Product Overview

Key-operated actuator, classic, maintained, 3 positions, MS1, 2 N/O, cable (black) with m8 plug, 4 pole, 1 m

Key Selector compact; Interlock; 3 positions; Key: MS1; 2; with cable 1 m and connector M8

Key-operated actuator, RMQ compact solution, maintained, 2 N/O, Cable (black) with M8 plug, 4 pole, 1 m, 3 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Not suitable for master key systems, 3 positions, Lock mechanism: MS1, I, II, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Auxiliary Control and Signalling Elements
--------------	---

Additional Product Information

Key-operated actuator, RMQ compact solution, maintained, 2 N/O, Cable (black) with M8 plug, 4 pole, 1 m, 3 positions, MS1, Bezel: titaniumKey-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with M8 plug, 4 pole, Cable Length: 1 m, Not suitable for master key systems, 3 positions, Lock mechanism: MS1, I, II, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)Delivery program Product rangeRMQ compact solutionBasic functionKey-operated buttonsSingle unit/Complete unitComplete

unitmaintainedFunction: [= spring-return]60° ? 60°Connection typeCable (black) with M8 plug, 4 poleCable Length1 mNot suitable for master key systems3 positionsLock mechanismMS1Key withdrawable in positionI0IIDegree of ProtectionIP66 (front)

IP65 (on rear)Front ringBezel: titaniumConnection to SmartWire-DTnoContactsN/O = Normally open2 N/OContact sequenceContact travel? = Contact closed? = Contact openContact diagramInformation about equipment suppliedWith 1 keyTechnical data

GeneralStandardsIEC/EN 60947-5-1

VDE 0660CertificationsCE, UL, CSALifespan, mechanical [Operations]> 1 x 106Operating frequency [Operations/h]? 100

Operating torque? 0.5 NmPlug tightening torque0.6 N/mTightening torque Threaded ring2 NmClimatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Degree of Pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRS3-MS1-K20-P32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.