

INDUSTRIAL COMPONENT DATA

C22-WRS3-MS1-K20-P65 186285 Y7-186285 EATON ELECTRIC

Key-operated actuator, classic, maintained, 3 positions..

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WRS3-MS1-K20-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WRS3-MS1-K20-P65
Catalog number	Y7-186285
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-9303ECA196
Generated	2026-08-06

Product Overview

Key-operated actuator, classic, maintained, 3 positions, MS1, 2 N/O, cable (black) with non-terminated end, 4 pole, 3.5 m
C22-WRS3-MS1-K20-P65

Eaton Moeller® series C22 Key-operated actuator, RMQ compact solution, maintained, 2 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, 3 positions, MS1, Bezel: titanium

Key-operated actuator, Product range: RMQ compact solution, Complete unit, maintained, Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, Not suitable for master key systems, 3 positions, Lock mechanism: MS1, I, II, Degree of Protection: IP66 (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66 (front), IP65 (on rear)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C22 Key-operated actuator Catalog Number 186285 Model Code

C22-WRS3-MS1-K20-P65 EAN 4015081817863 Product Length/Depth 3597 mm Product Height 30 mm Product Width 30 mm Product Weight 0.143 kg Certifications CE

VDE 0660

IEC/EN 60947-5-1

CSA

UL

CSA File No.: 165628

CSA Class No.: 321103

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL listed, CSA certified Catalog Notes Not suitable for master key systems Product specifications

Type Key-operated button Accessories 1 key included with supplied equipment. Actuator color Black Product Category

RMQ compact solution Actuator function Key withdrawable in position 1

Switching function latching

Key withdrawable in position 0

Maintained

Key withdrawable in position 2 Electric connection type Other Fitted with: Front ring Operating frequency 100 Operations/h

Pollution degree 3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Connection to SmartWire-DT No Rated impulse withstand voltage (Uimp) 800 V AC

Actuator type Key Actuator diameter 4.7 mm Ambient operating temperature - max 70 °C Ambient operating temperature -

min -30 °C Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of

contacts (normally open contacts) 2 Opening diameter 22.5 mm Opening height 0 mm Operating torque 0.5 Nm Rated

insulation voltage (Ui) 250 V Rated operati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WRS3-MS1-K20-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.