

INDUSTRIAL COMPONENT DATA

C22-WS-MS1-K20 132800 EATON ELECTRIC C22-WS-MS1-K20

Brand: EATON - MOELLER | Manufacturer Part Number: C22-WS-MS1-K20



Manufacturer	EATON - MOELLER
MPN / Reference	C22-WS-MS1-K20
Catalog number	132800
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-4369F40189
Generated	2026-08-06

Product Overview

C22-WS-MS1-K20

Key-operated actuator, RMQ Compact, momentary, 2 N/O, Screw connection, 2 positions, MS1, Bezel: titanium
Key-operated actuator, Product range: RMQ Compact, Complete unit, momentary, Screw connection, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

Key-operated actuator, RMQ Compact, momentary, 2 N/O, Screw connection, 2 positions, MS1, Bezel: titanium
Key-operated actuator, Product range: RMQ Compact, Complete unit, momentary, Screw connection, Not suitable for master key systems, 2 positions, Lock mechanism: MS1, Degree of Protection: IP66, Bezel: titanium, Connection to SmartWire-DT: no, With 1 key, Standards: IEC/EN 60947-5-1, VDE 0660, Degree of Protection: IP66
Delivery program
Product range
RMQ Compact
Basic function
Key-operated buttons
Single unit/Complete unit
Complete unit
momentary
Function: [= spring-return]
40°
Connection type
Screw connection
Not suitable for master key systems
2 positions
Lock mechanism
MS1
Key withdrawable in position 0
Degree of Protection
IP66
Front ring
Bezel: titanium
Connection to SmartWire-DT
no
Contacts
N/O = Normally open
2 N/O
Contact sequence
Contact travel? = Contact closed? = Contact open
Contact diagram
Information about equipment supplied
With 1 key
Technical data
General
Standards
IEC/EN 60947-5-1
VDE 0660
Lifespan, mechanical [Operations]> 0.1 x 106
Operating frequency [Operations/h]? 100
Operating torque? 0.5 Nm
Climatic proofing
Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Degree of Protection IP66 Mounting position As required Terminal capacities Solid 2 x 0.5 - 1.5 mm² Terminal capacities Flexible with ferrule 2 x 0.5 - 1.5 mm² Tightening torque for terminal screw 0.8 Nm Contacts Rated impulse withstand voltage [Uimp] 4000 V AC Rated insulation voltage [Ui] 250 V Rated conditional short-circu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22-WS-MS1-K20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.