

## INDUSTRIAL COMPONENT DATA

# C22G80 EATON ELECTRIC Fuse-link, LV, 10 A, AC 690 V, 22 x 58 mm, gL/gG, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: C22G80



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | C22G80           |
| Catalog number  | 10000            |
| Category        | Cylindrical fuse |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-A5352B55D4    |
| Generated       | 2026-08-06       |

## Product Overview

CYLINDRICAL FUSE 22 x 58 80A GG 500V AC

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 80 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH22 Modular fuse holder

Fuse, fuse-link, low voltage, 80 A, AC 500 V, 22 x 58 mm, gL/gG, IEC, cylindrical, for industrial applications, for general purpose use, IEC 60269-2

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Bussmann Series Low Voltage fuses and accessories

## Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage cylindrical fuse Catalog Number C22G80 EAN 5027590495561 UPC 051712754507 Product Length/Depth 58 mm Product Height 22.2 mm Product Width 22.2 mm Product Weight 55 g

Compliances CE Marked

GoST-R

RoHS Compliant Certifications IEC 60269 Electrical data

Amperage Rating 80 A Voltage rating 500 V Voltage type AC Breaking capacity 120 kA Utilization category gG (cable protection/equipment protection) Frequency rating - max 62 Hz Compatible fuse holder

Suitable for CH22 Modular fuse holder

ETIM for C22G80 Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

22x58 mm

Voltage type (EF000187)

AC

Rated current (EF000227)

80 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

7.8 W

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22G80 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.