

## INDUSTRIAL COMPONENT DATA

# C30C-FD-R-K01-P65 185960 Y7-185960 EATON ELECTRIC

## C30C-FD-R-K01-P65

Brand: EATON - MOELLER | Manufacturer Part Number: C30C-FD-R-K01-P65



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | EATON - MOELLER       |
| MPN / Reference | C30C-FD-R-K01-P65     |
| Catalog number  | Y7-185960             |
| Category        | Push button, complete |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-7AF0506F57         |
| Generated       | 2026-08-05            |

### Product Overview

C30C-FD-R-K01-P65

Eaton Moeller® series C30 Pushbutton, Flat, momentary, 1 NC, Cable (black) with non-terminated end, 4 pole, 3.5 m, red, Blank, Metal bezel

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: red, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Metal bezel, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

### Additional Product Information

General specifications

Product Name Eaton Moeller® series C30 Pushbutton Catalog Number 185960 Model Code C30C-FD-R-K01-P65 EAN 4015081814619 Product Length/Depth 3560 mm Product Height 46 mm Product Width 36 mm Product Weight 0.139 kg

Certifications IEC/EN 60947-5-1

VDE 0660

CSA Class No.: 321103

CSA File No.: 165628

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

UL

CSA Catalog Notes Contacts with safety function, by positive opening to IEC/EN 60947-5-1 Features & Functions

Bezel color Chrome Bezel material Metal Design Flat

Cable end open Electric connection type Cable Features Positive opening Fitted with: Front ring Inscription Blank General

Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with

non-terminated end, 4 pole Degree of protection NEMA Other

IP67/IP69K Mounting position As required Opening diameter 30.5 mm Operating frequency 3600 Operations/h Overvoltage

category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC

Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 2 Nm, Threaded ring Type Pushbutton

actuator Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

-30 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constan...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C30C-FD-R-K01-P65 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.