

INDUSTRIAL COMPONENT DATA

**C30C-FDR-W-K10-P65 185968 Y7-185968 EATON ELECTRIC
C30C-FDR-W-K10-P65**

Brand: EATON - MOELLER | Manufacturer Part Number: C30C-FDR-W-K10-P65



Manufacturer	EATON - MOELLER
MPN / Reference	C30C-FDR-W-K10-P65
Catalog number	Y7-185968
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-566224C02F
Generated	2026-08-05

Product Overview

C30C-FDR-W-K10-P65

Eaton Moeller® series C30 Pushbutton, Flat, maintained, 1 N/O, Cable (black) with non-terminated end, 4 pole, 3.5 m, White, Blank, Metal bezel

Pushbutton, RMQ compact solution, Complete unit, Design: Flat, maintained, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 3.5 m, button plate: White, Button plate Blank, Name: None, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Metal bezel, Connection to SmartWire-DT: no, N/O = Normally open: 1 N/O, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C30 Pushbutton Catalog Number 185968 Model Code C30C-FDR-W-K10-P65 EAN 4015081814695 Product Length/Depth 3560 mm Product Height 46 mm Product Width 36 mm Product Weight 0.139 kg

Certifications IEC/EN 60947-5-1

VDE 0660

CSA Class No.: 321103

CSA File No.: 165628

UL 508

CSA-C22.2 No. 14-18 and No. 94.2-15

CE marking

UL Category Control No.: NKCR

UL File No.: E29184

UL

CSA Features & Functions

Bezel color Chrome Bezel material Metal Design Flat

Cable end open Electric connection type Cable Fitted with: Front ring Inscription Blank General

Cable length 3.5 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated end, 4 pole Degree of protection NEMA Other

IP67/IP69K Mounting position As required Opening diameter 30.5 mm Operating frequency 3600 Operations/h Overvoltage

category III Pollution degree 3 Product category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC

Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 2 Nm, Threaded ring Type Pushbutton

actuator Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min

-30 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated insulation volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C30C-FDR-W-K10-P65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.