

INDUSTRIAL COMPONENT DATA

**C30C-FL-B-24-P5 186013 Y7-186013 EATON ELECTRIC
C30C-FL-B-24-P5**

Brand: EATON - MOELLER | Manufacturer Part Number: C30C-FL-B-24-P5



Manufacturer	EATON - MOELLER
MPN / Reference	C30C-FL-B-24-P5
Catalog number	Y7-186013
Category	Indicator light complete
Minimum order	1 Pcs
Document ID	EO-B37800286D
Generated	2026-08-03

Product Overview

C30C-FL-B-24-P5

Eaton Moeller® series C30 Indicator light, Flat, Cable (black) with M12A plug, 4 pole, 1 m, Lens Blue, LED Blue, 24 V AC/DC

Indicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with M12A plug, 4 pole, Cable Length: 1 m, Color Lens: Blue, Color LED: Blue, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Auxiliary Control and Signalling Elements

Additional Product Information

General specifications

Product Name Eaton Moeller® series C30 Indicator light Catalog Number 186013 Model Code C30C-FL-B-24-P5 EAN 4015081815142 Product Length/Depth 1060 mm Product Height 46 mm Product Width 36 mm Product Weight 0.074 kg Certifications VDE 0660

IEC/EN 60947-5-1 Features & Functions

Bezel color Chrome Bezel material Metal Design Flat

M12A Electric connection type Other Fitted with: Front ring

Light source Lens color Blue Light color Blue General

Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with M12A plug, 4

pole Degree of protection IP Other

NEMA Other Mounting position As required Opening diameter 30 mm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 2 Nm, Threaded ring

1 Nm, Plug Type Indicator lights Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated insulation voltage (Ui) 30 V Rated operational voltage 24 V AC/DC (LED) Rated operational voltage (Ue) - min 24 V Rated operational voltage (Ue) - max 24 V Short-circuit protection rating

Max. 4 A gG/gL, Fuse, Contacts Actuator

Actuator diameter 4.7 mm

ETI...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C30C-FL-B-24-P5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.