

## INDUSTRIAL COMPONENT DATA

**C30C-FL-Y-24-P62 185956 Y7-185956 EATON ELECTRIC  
C30C-FL-Y-24-P62**

Brand: EATON - MOELLER | Manufacturer Part Number: C30C-FL-Y-24-P62



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | C30C-FL-Y-24-P62         |
| Catalog number  | Y7-185956                |
| Category        | Indicator light complete |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-8890B75EAB            |
| Generated       | 2026-08-03               |

**Product Overview**

C30C-FL-Y-24-P62

Eaton Moeller® series C30 Indicator light, Flat, Cable (black) with non-terminated end, 4 pole, 1 m, Lens yellow, LED white, 24 V AC/DC

Indicator light, Product range: RMQ compact solution, Complete unit, Design: Flat, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 1 m, Color Lens: yellow, Color LED: white, Rated operational voltage LED: 24 V AC/DC, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Connection to SmartWire-DT: no, Standards: IEC/EN 60947-5-1, VDE 0660

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Auxiliary Control and Signalling Elements

**Additional Product Information**

## General specifications

Product Name Eaton Moeller® series C30 Indicator light Catalog Number 185956 Model Code C30C-FL-Y-24-P62 EAN 4015081814572 Product Length/Depth 1060 mm Product Height 46 mm Product Width 36 mm Product Weight 0.063 kg Certifications IEC/EN 60947-5-1

## VDE 0660 Features &amp; Functions

Bezel color Chrome Bezel material Metal Design Flat

Cable end open Electric connection type Other Fitted with: Light source

Front ring Lens color Yellow Light color White General

Cable length 1 m Cable material PUR Connection to SmartWire-DT No Connection type Cable (black) with non-terminated

end, 4 pole Degree of protection IP Other

NEMA Other Mounting position As required Opening diameter 30 mm Overvoltage category III Pollution degree 3 Product Category RMQ compact solution Rated impulse withstand voltage (Uimp) 800 V AC Shock resistance 30 g, Mechanical, Shock duration 11 ms Tightening torque 2 Nm, Threaded ring Type Indicator lights Voltage type AC/DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Electrical rating

Rated conditional short-circuit current (Iq) 1 kA Rated insulation voltage (Ui) 30 V Rated operational voltage 24 V AC/DC (LED) Rated operational voltage (Ue) - min 24 V Rated operational voltage (Ue) - max 24 V Short-circuit protection rating

Max. 4 A gG/gL, Fuse, Contacts Actuator

Actuator diamete...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C30C-FL-Y-24-P62 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.