

INDUSTRIAL COMPONENT DATA

SWD4-8FRF-10 121377 Y7-121377 EATON ELECTRIC Cable adapter, SmartWire-DT, flat to round cable

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-8FRF-10



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-8FRF-10
Catalog number	Y7-121377
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-803F257663
Generated	2026-08-05

Product Overview

Cable adapter, SmartWire-DT, flat to round cable

SWD4-8FRF-10

Eaton SWD4 Cable adapter, SmartWire-DT, flat to round cable

SmartWire-DT cable adapter, enables the transition between the SWD4-LF SWD ribbon cable and SWD4-...LR8-24 round cable, connection SWD ribbon cable via SWD4-8MF2 flat cable 8 pole

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Smartwire Darwin**

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Cable adapter Catalog Number 121377 Model Code SWD4-8FRF-10 EAN 4015081192069 Product Length/Depth 36 mm Product Height 90 mm Product Width 35 mm Product Weight 0.041 kg

Certifications CSA Class No.: 3211-07

UL File No.: E29184

CSA File No.: 2324643

EN 50178

UL

UL Category Control No.: NKCR

IEC/EN 61131-2

CSA Catalog Notes not relevant General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Mounting method Top-hat rail fixing (according to IEC/EN 60715, 35 mm)

Screw fixing using fixing brackets ZB4-101-GF1 (accessories) Product category SmartWire-DT accessories Type Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures

Operating temperature - min -25 °C Operating temperature - max 55 °C Relative humidity 0 - 95 % (non-condensing, IEC/EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-8FRF-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.