

INDUSTRIAL COMPONENT DATA

SWD4-FFR-ST1-1 168881 Y7-168881 EATON ELECTRIC SWD cable adapter for putting together a local SWD segment

Brand: EATON - MOELLER | Manufacturer Part Number: SWD4-FFR-ST1-1



Manufacturer	EATON - MOELLER
MPN / Reference	SWD4-FFR-ST1-1
Catalog number	Y7-168881
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-C9213F66E1
Generated	2026-08-04

Product Overview

SWD cable adapter for putting together a local SWD segment

SWD4-FFR-ST1-1

Adapter for the surface mounting of a local SWD segment in combination with the power feeder module SWD4-FFR-PF1-1, connection of the local SWD segments via ribbon cable SWD4-...LF8-24

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Smartwire Darwin

Additional Product Information

General specifications

Product Name Eaton SWD4 Accessory Adapter Catalog Number 168881 Model Code SWD4-FFR-ST1-1 EAN 4015081653720 Product Length/Depth 34 mm Product Height 90 mm Product Width 35 mm Product Weight 0.046 kg

Certifications IEC/EN 61131-2

EN 50178 Catalog Notes not relevant General

Degree of protection IP20

IP20 (according to IEC/EN 60529, EN 50178, VBG 4) Mounting method Screw fixing using fixing brackets ZB4-101-GF1 (accessories)

Top-hat rail fixing (according to IEC/EN 60715, 35 mm) Product category SmartWire-DT accessories Type Ambient conditions, mechanical

Constant acceleration 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations Constant amplitude 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations Mounting position As required Shock resistance 15 g, Mechanical, according to

IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 70 °C Climatic proofing Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3 Environmental conditions Condensation: prevent with appropriate measures Operating temperature - min -25 °C Operating temperature - max 55 °C Relative humidity 0 - 95 % (non-condensing, IEC/EN 60068-2-30) Electro magnetic compatibility

Air discharge 8 kV, according to IEC 61131-2, level 3, ESD Con...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SWD4-FFR-ST1-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.