

INDUSTRIAL COMPONENT DATA

V-M12 215078 Y7-215078 EATON ELECTRIC Cable gland, M12, RAL 7035, IP68 x

Brand: EATON - MOELLER | Manufacturer Part Number: V-M12



Manufacturer	EATON - MOELLER
MPN / Reference	V-M12
Catalog number	Y7-215078
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-C85A0E6507
Generated	2026-08-04

Product Overview

Cable gland, M12, RAL 7035, IP68_x

V-M12

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Cable gland, M12, RAL 7035, IP68

Cable gland, cable entry=M12, drilling dimensions = 12.5mm, utilization cable NYM/NYY, 4-wire=H03VV-F3x0.75, NYM 1x2.5mm², degree of protection IP68 to 5 bar (30min), polyamide, halogen free, RAL 7035, with lock nut and built-in strain relief, flammability classification V2 according to UL94

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear Catalog Number 215078 Model Code V-M12 EAN 4015082150785 Product Length/Depth 50 mm Product Height 20 mm Product Width 20 mm Product Weight 0.007 kg Compliances RoHS conform Product specifications

Used with NYM 2.5 mm² (1x)H03VV-F 0.75 mm² (3x) Surface finishing RAL 7035, light gray Special features Type General switchboard accessory

Chemical resistance Resistant against: acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes Material Polyamide

Plastic

Halogen free Color Gray Nominal thread size Metric/PG 12 Nominal thread size inch/gas pipe thread Other Pitch thread 1.5 mm Thread Length 7 mm Wrench width 19 mm Hexagon angular dimension 0 mm Suitable for cable diameter - max 8 mm Suitable for cable diameter - min 3 mm Material quality Polyamide (PA) Surface protection Untreated Degree of protection (IP) IP68 Model Straight Type of sealing Cut-out ring For ex-zone gas None For ex-zone dust None Temperature resistance -20 °C - 100 °C, short-time up to approx. 120 °C Fitted with: Locknut Strain Relief Flammability characteristics (UL) V2 (UL94) Lamp type included Halogen Free Flame retardant Glow wire test 750 °C according to EN 60695-2-11 Thread type Metric Protection, proofing and resistance Shock Resistant Accessory/spare part type Cable management Stress fracture risk Low Opening diameter 12.5 mm Operating temperature - max....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / V-M12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.