

INDUSTRIAL COMPONENT DATA

V-M16 215077 Y7-215077 EATON ELECTRIC Cable gland, M16, RAL 7035, IP68 x

Brand: EATON - MOELLER | Manufacturer Part Number: V-M16



Manufacturer	EATON - MOELLER
MPN / Reference	V-M16
Catalog number	Y7-215077
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-0D378F49AB
Generated	2026-08-05

Product Overview

Cable gland, M16, RAL 7035, IP68_x

V-M16

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Cable gland, M16, RAL 7035, IP68

Cable gland, cable entry=M16, drilling dimensions=16.5mm, utilization cable NYM/NYY, 4-wire=H05VV-F3x1.5, NYM 1x16/3x1.5mm², degree of protection IP68 to 5 bar (30min), polyamide, halogen free, RAL 7035, with lock nut and built-in strain relief, flammability classification V2 according to UL94

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear Catalog Number 215077 Model Code V-M16 EAN 4015082150778 Product Length/Depth 50 mm Product Height 20 mm Product Width 20 mm Product Weight 0.01 kg Compliances RoHS conform Product specifications

Used with NYM 16 mm² (1x) or 1.5 mm² (3x)

H05VV-F 1.5 mm² (3x) Surface finishing RAL 7035, light gray Special features Type General switchboard accessory

Chemical resistance Resistant against: acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes Material Plastic

Polyamide

Halogen free Color Gray Nominal thread size Metric/PG 16 Nominal thread size inch/gas pipe thread Other Pitch thread 1.5 mm Thread Length 9 mm Wrench width 24 mm Hexagon angular dimension 0 mm Suitable for cable diameter - max 10 mm Suitable for cable diameter - min 4.5 mm Material quality Polyamide (PA) Surface protection Untreated Degree of protection (IP) IP68 Model Straight Type of sealing Cut-out ring For ex-zone gas None For ex-zone dust None Temperature resistance -20 °C - 100 °C, short-time up to approx. 120 °C Fitted with: Locknut Strain Relief Flammability characteristics (UL) V2 (UL94) Lamp type included Halogen Free Flame retardant Glow wire test 750 °C according to EN 60695-2-11 Thread type Metric Protection, proofing and resistance Shock Resistant Accessory/spare part type Cable management Stress fracture risk Low Opening diameter 16.5 mm Operating te...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / V-M16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.