

INDUSTRIAL COMPONENT DATA

V-M20 206910 Y7-206910 EATON ELECTRIC Cable gland, M20, RAL 7035, IP68 x

Brand: EATON - MOELLER | Manufacturer Part Number: V-M20



Manufacturer	EATON - MOELLER
MPN / Reference	V-M20
Catalog number	Y7-206910
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-67AD936B94
Generated	2026-08-04

Product Overview

Cable gland, M20, RAL 7035, IP68_x

V-M20

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Cable gland, M20, RAL 7035, IP68

Cable gland, cable entry=M20, drilling dimensions=20.5mm, utilization cable NYM/NYY, 4-wire=H05VV-F4x2.5/3x4, NYM 5x1.5/5x2.5mm², degree of protection IP68 to 5 bar (30min), polyamide, halogen free, RAL 7035, with lock nut and built-in strain relief, flammability classification V2 according to UL94

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear Catalog Number 206910 Model Code V-M20 EAN 4015082069100 Product Length/Depth 140 mm Product Height 85 mm Product Width 81 mm Product Weight 0.015 kg Compliances RoHS conform Certifications IEC/EN 60947

VDE 0660 Catalog Notes OBSOLETE SEE SUPERSEDURE Product specifications

Pollution degree 3 Surface finishing RAL 7035, light gray Used with Cable glands

H05VV-F 2.5 mm² (4x) or 4 mm² (3x)

NYM 1.5 mm² (5x) or 2.5 mm² (5x)

General switchboard accessory

Accessory Special features Type Accessory

General switchboard accessory

Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Connection to SmartWire-DT No connection to SmartWire-DT Chemical resistance

Resistant against: acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes Material Plastic

Polyamide

Halogen free NEMA Rating UL/CSA Type 3R, 4X, 12, 13

1 Color Gray Mounting position As required Nominal thread size Metric/PG 20 Nominal thread size inch/gas pipe thread

Other Pitch thread 1.5 mm Thread Length 10 mm Wrench width 30 mm Hexagon angular dimension 0 mm Suitable for

cable diameter - max 13 mm Suitable for cable diameter - min 6 mm Material quality Polyamide (PA) Surface protection

Untreated Degree of protection (IP) IP68 Model Straight Type of sealing Cut-out ring For ex-zone gas None For ex-zone

dust None Overvoltage category III Tem...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / V-M20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.