

INDUSTRIAL COMPONENT DATA

V-M50 206913 Y7-206913 EATON ELECTRIC Cable gland, M50, RAL 7035, IP68 x

Brand: EATON - MOELLER | Manufacturer Part Number: V-M50



Manufacturer	EATON - MOELLER
MPN / Reference	V-M50
Catalog number	Y7-206913
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-0EA50909B5
Generated	2026-08-06

Product Overview

Cable gland, M50, RAL 7035, IP68_x

V-M50

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Cable gland, M50, RAL 7035, IP68

Cable gland, cable entry=M50, drilling dimensions=50.5mm, utilization cable NYM/NYY, 4-wire=NYM 4x35/5x25mm², degree of protection IP68 to 5 bar (30min), polyamide, halogen free, RAL 7035, with lock nut and built-in strain relief, flammability classification V2 according to UL94

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories cable gland metric Catalog Number 206913 Model Code V-M50 EAN 4015082069131 Product Length/Depth 80 mm Product Height 50 mm Product Width 50 mm Product Weight 0.114 kg

Compliances RoHS conform Product specifications

Surface finishing RAL 7035, light gray Used with NYM 35 mm² (4x) or 25 mm² (5x) Special features Type General switchboard accessory Chemical resistance Resistant against: acetone, petrol, paraffin, diesel, grease, oil, solvent for paints and varnishes Material Halogen free

Polyamide

Plastic Color Gray Nominal thread size Metric/PG 50 Nominal thread size inch/gas pipe thread Other Pitch thread 1.5 mm

Thread Length 14 mm Wrench width 55 mm Hexagon angular dimension 0 mm Suitable for cable diameter - max 35 mm
Suitable for cable diameter - min 21 mm Material quality Polyamide (PA) Surface protection Untreated Degree of protection
(IP) IP68 Model Straight Type of sealing Cut-out ring For ex-zone gas None For ex-zone dust None Temperature resistance
-20 °C - 100 °C, short-time up to approx. 120 °C Fitted with: Locknut
Strain Relief Flammability characteristics (UL) V2 (UL94) Lamp type included Halogen Free Flame retardant Glow wire test
750 °C according to EN 60695-2-11 Thread type Metric Protection, proofing and resistance Shock Resistant
Accessory/spare part type Cable management Stress fracture risk Low Opening diameter 50.5 mm Operating temperature -
max 120 °C Operating temperature - min -20 °C Outer c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / V-M50 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.