

INDUSTRIAL COMPONENT DATA

DILM400-XKU-S 208293 Y7-208293 EATON ELECTRIC Cable terminal block, for DILM250-400

Brand: EATON - MOELLER | Manufacturer Part Number: DILM400-XKU-S



Manufacturer	EATON - MOELLER
MPN / Reference	DILM400-XKU-S
Catalog number	Y7-208293
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-232BE8E243
Generated	2026-08-04

Product Overview

Cable terminal block, for DILM250-400

DILM400-XKU-S

Eaton Moeller® series DILM Cable terminal block, for DILM250-400

Cable terminal block for contactor DILM250, DILM300A and DILM400

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors more than 170 A
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM cable terminal block Catalog Number 208293 Model Code DILM400-XKU-S

EAN 4015082082932 Product Length/Depth 117 mm Product Height 30 mm Product Width 133 mm Product Weight 0.66 kg

Certifications CSA Class No.: 3211-04

CSA File No.: 012528

IEC/EN 60947-4-1

UL

CSA

UL File No.: E29184

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

CE

UL 508 Catalog Notes Consisting of 3 box terminals Global

Accessory/spare part type Connection terminal Connection Connection options: round conductors, flexible and stranded, ribbon cables. Fitted with: Control cable connection Product category Accessories General

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Fitted with: Control cable connection Product category Accessories Climatic environmental conditions

Terminal capacity 2 x (0.75 - 4) mm², solid, Control circuit cables

1 x (120 - 300) mm², solid, Main cables

2 x (70 - 240) mm², solid, Main cables

1 x (95 - 240) mm², flexible with ferrule, Main cables

2 x (70 - 185) mm², flexible with ferrule, Main cables

1 x (10 x 16 x 0.8) mm (Number of segments x width x thickness), Flat conductor, Main cable

2 x (20 x 24 x 0.5) mm (Number of segments x width x thickness), Flat conductor, Main cable

2 x (11 x 21 x 1) mm (Number of segments x width x thickness), Flat conductor, Main cable

1 x (250 -600 MCM)

2 x (2/0 AWG-500 MCM)

20 Nm, Screw terminals, Main cables

1 x (0.75 - 4) mm², solid, Control circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM400-XKU-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.