

INDUSTRIAL COMPONENT DATA

T5-3-SOND*/I5 207530 Y7-207530 EATON ELECTRIC

Non-standard switch, T5, 100 A, surface mounting, 3 contact un..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-3-SOND*/I5



Manufacturer	EATON - MOELLER
MPN / Reference	T5-3-SOND*/I5
Catalog number	Y7-207530
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-9A7117F24B
Generated	2026-08-05

Product Overview

Non-standard switch, T5, 100 A, surface mounting, 3 contact unit(s)

T5-3-SOND*/I5

Eaton Moeller® series T5 Non-standard switch, T5, 100 A, surface mounting, 3 contact unit(s)

Non-standard switch, Product range: Non-standard switch, Part group reference: T5, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Non-standard switch Catalog Number 207530 Model Code T5-3-SOND*/I5

Product Length/Depth 280 mm Product Height 197 mm Product Width 200 mm Product Weight 1.856 kg Certifications

IEC/EN 60947

IEC/EN 60947-3

VDE 0660

IEC/EN 60204

ETIM for 207530 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

No

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Rated operating voltage (EF001435)

690 V

Rated permanent current I_u (EF001389)

100 A

Rated permanent current at AC-23, 400 V (EF011777)

100 A

Rated permanent current at AC-21, 400 V (EF009165)

100 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current I_{cw} (EF007050)

1.7 kA

Rated operation power at AC-23, 400 V (EF007027)

55 kW

Switching power at 400 V (EF009166)

55 kW

Conditioned rated short-circuit current I_q (EF001444)

2 kA

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)

Complete device in housing

Suitable for front...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-3-SOND*/I5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.