

INDUSTRIAL COMPONENT DATA

TM-1-SOND-ERSTBESTELLUNG/IVS 225347 Y7-225347

EATON ELECTRIC Non-standard switch, TM, 10 A, service distribu..

Brand: EATON - MOELLER | Manufacturer Part Number: TM-1-SOND-ERSTBESTELLUNG/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	TM-1-SOND-ERSTBESTELLUNG/IVS
Catalog number	Y7-225347
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-62E0508D1B
Generated	2026-08-06

Product Overview

Non-standard switch, TM, 10 A, service distribution board mounting, 1 contact unit(s)

TM-1-SOND-ERSTBESTELLUNG/IVS

Non-standard switch, TM, 10 A, service distribution board mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first time

Non-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP30, Design: service distribution board mounting, 1 contact unit(s), Rated uninterrupted current: I_u= 10 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Non-standard switch, TM, 10 A, service distribution board mounting, 1 contact unit(s), customized version according to form, TM mini rotary switches, ordering for the first timeNon-standard switch, Product range: Non-standard switch, Standards: IEC/EN 60947, VDE 0660, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1, Part group reference: TM, customized version according to form, TM mini rotary switches, ordering for the first time, Degree of Protection: Front IP30, Design: service distribution board mounting, 1 contact unit(s), Rated uninterrupted current: I_u= 10 A
Delivery program

Product rangeNon-standard switchPart group referenceTMNotescustomized version according to formNon-standard orderTM mini rotary switches, ordering for the first timeDegree of ProtectionFront IP30Designservice distribution board mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]3 kWRated uninterrupted current [Iu]10 ANote on rated uninterrupted current IuRated uninterrupted current Iuis specified for max. cross-section.Number of contact units1 contact unit(s)Design verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]10 AHeat dissipation per pole, current-dependent [Pvid]0.15 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperatur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-1-SOND-ERSTBESTELLUNG/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.