

INDUSTRIAL COMPONENT DATA

CCP-1-30M EATON ELECTRIC Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P,..

Brand: EATON - MOELLER | Manufacturer Part Number: CCP-1-30M



Manufacturer	EATON - MOELLER
MPN / Reference	CCP-1-30M
Catalog number	CCP130M
Category	Fuse switch disconnector
Minimum order	6 Pcs
Document ID	EO-21B52F6526
Generated	2026-08-06

Product Overview

Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC
Comp Circuit Protec 1Pole 10X38MM Midget - Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC
Comp Circuit Protec 1Pole 10X38MM Midget

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEControl, Fused disconnector, low voltage, 30 A, AC 240 V, UL midget, IEC 10 x 38, AC23A, 1P, UL, IEC, fuse-links FNM, FNQ, KTK, BAF, KLM, UL 508, IP20, Breaking Capacity 10 kADelivery program
Product rangeControlBasic functionFused disconnectorField of applicationlow voltageRated current [I]30 ARated voltageAC 240 VConstruction sizeUL midget
IEC 10 x 38Utilization categoryAC23AProtectionIP20Breaking Capacity10 kANumber of poles1Pusable for size/applicationsfuse-links FNM, FNQ, KTK, BAF, KLMStandard/ApprovalUL
IECStandards/RegulationsUL 508Technical data ETIM 7.0
Low-voltage industrial components (EG000017) / Fuse switch disconnector (EC001040)Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnector ( [AKF058013])Version as main switchNoVersion as safety switchNoMax. rated operation voltage Ue AC240 VRated permanent current Iu30 ARated operation power at AC-23, 400 VkWConditioned rated

short-circuit current Iq10 kARated short-time withstand current Icw10 kASuitable for fusesOtherNumber of poles1With error protectionNoType of electrical connection of main circuitScrew connectionCable entryOtherEquipped with connectorsYesSuitable for ground mountingNoSuitable for front mounting 4-holeNoSuitable for busbar mountingYesType of control elementRocker leverPosition...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CCP-1-30M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.