

INDUSTRIAL COMPONENT DATA

100M125 415V AC BS88 FUSE CD100M125 EATON ELECTRIC

Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, 3..

Brand: EATON - MOELLER | Manufacturer Part Number: 100M125 415V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	100M125 415V AC BS88 FUSE
Catalog number	CD100M125
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-2D10FD5EEA
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 50 A, AC 415 V, BS88/J, 31 x 131 mm, gL/gG, BS

100M125 415V AC BS88 FUSE

Eaton Bussmann series low voltage British standard fuse, Fuse-link, LV, 100 A, AC 415 V, BS88/B1, 26 x 126 mm, gM, BS, 100M125

Fuse, Fuse-link, low voltage, 100 A, AC 415 V, BS88/B1, 26 x 126 mm, gM, BS, centre-bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder RS200

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number CD100M125 EAN

5027590496131 UPC 051712844833 Product Length/Depth 126 mm Product Height 26 mm Product Width 26 mm Product Weight 107.9 g Compliances Contact Manufacturer Product specifications

Type Fuse Application general industrial applications Amperage Rating 125 A Fitted with: Centre bolted tags Fuse size BS88/B1 Current type AC Mounting dimension M8 Center-to-center distance of connections 111 mm Breaking capacity 80 kA Rated switching capacity 80 kA Motor current rating 100M125 Rated voltage AC 415 V Class Class gM Fuse type CD Utilization category gM (motor protection) Color None Interrupt rating 80 kAIC Fuse indicator None Insulated metal gripping lugs (IMGL) No Watt losses 11 W Connection 111 mm fixing centre Construction BS88/B1 Construction size B1 Fuse shape Center bolted tags Voltage type AC Voltage rating 415 V Fuse system (according to IEC 60269) Fuse system E

ETIM for CD100M125 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

B1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

415 V

Rated current (EF000227)

125 A

Utilization category according to IEC 60269 (EF002572)

gM (motor protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 100M125 415V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.